



Military Speedfix – A New Versatile External Fixator for Combat Injuries

H. Gerngross, MD

Military Hospital Ulm-Germany Oberer Eselsberg 40, D-89075 Ulm

ABSTRACT

External fixators are the first joice for severe comminuted fractures in long bones on the battlefield. The applied fixators of the different medical services in the NATO are mostly bulky in shape, difficult to mount, unstable or too complex to understand.

It was the intend of the NATO working group STANAG 2469 to improve the standards for the external fixation of long bones. The italian proposal for a general fixation system was opposed by the US and German delegies in terms of lack of reducability after mounting, questionable stability and applicability.

The German group favourises a special military fixator on the basis of the Speedfix (Smith&Nephew). A special design allows the fixation of the clamp for one fragment in one step by one screw or leverarm. The weight, versatility and stability of the new fixator were tested and found to be stable enough also for the femur. It is reduceable after mounting and easy to understand (one bar system). The price is also comparable to the common systems on the market.

The clinical tests are now under observations. The acceptance by the surgeons is high, the duration of implantation short, and the stability excellent. So we conclude, that the new military speedfix can probably replace the older systems.

INTRODUCTION

The only option of stabilisation complex fractures of long bones in the field is the external fixator. It allows in a simple and undangerous way the primary stabilisation, also in multiple trauma patients. The general advantages of the external fixation in long bones is the facilitation of transport, reduction of fractur pain and the protection of soft tissues and vessels. Also the symptoms of shoc an be reduced. No further extension device is necessary in comminuted or defect fractures. It is also assumed that the stabilisation away from the fracture zone could prevent infection and facilitates the bone and soft tissue debridement. Comples systems cannot fullfill the requirements for military purposes in many ways.

So it was proposed to design not a simple, but simple to understand system, that is versatile to handle, variable for all locations on long bones, ist should have only one screw for thightening one element, has to be reducable and inexpensive.

The International Standardization Agreement Ratification –STANAG 2469 / EXTERNAL FIXATION DEVICES FOR BONE INJURIES describes a single bar external bone fixator that is able to hold long bone fragments in place for transportation of the casualty. The fixator has to be stable enough to avoid secondary dislocation during transportation, and must allow the alignment also when it is in place. External fixation in the field is usually necessary for the lower extremities and pelvis. Upper extremity injuries can usually be initially treated with splinting or casting until they reach a definitive care facility. For transport, single bar fixation may be adequate depending on fracture and patient characteristics. It is

Paper presented at the RTO HFM Symposium on "Combat Casualty Care in Ground Based Tactical Situations: Trauma Technology and Emergency Medical Procedures", held in St. Pete Beach, USA, 16-18 August 2004, and published in RTO-MP-HFM-109.

RTO-MP-HFM-109 17 - 1

Report Documentation Page				Form Approved OMB No. 0704-0188		
Public reporting burden for the col maintaining the data needed, and c including suggestions for reducing VA 22202-4302. Respondents shot does not display a currently valid G	ompleting and reviewing the collect this burden, to Washington Headqu ald be aware that notwithstanding as	tion of information. Send comment parters Services, Directorate for Inf	s regarding this burden estimate ormation Operations and Reports	or any other aspect of t s, 1215 Jefferson Davis	his collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE 2. REPORT TYPE				3. DATES COVERED		
01 SEP 2004		N/A		_		
4. TITLE AND SUBTITLE Military Speedfix A New Versatile External Fixator for Combat Injuries				5a. CONTRACT NUMBER		
				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Military Hospital Ulm-Germany Oberer Eselsberg 40, D-89075 Ulm				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited						
13. SUPPLEMENTARY NO See also ADM0017 and Emergency Mo technologies des tra images.	95, Combat Casualt edical Procedures (S	Soins aux blessés au	combat dans des	situations ta	ctiques :	
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFIC		17. LIMITATION OF	18. NUMBER	19a. NAME OF		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ABSTRACT UU	OF PAGES 2	RESPONSIBLE PERSON	



not, however adequate for definitive fixation. Additional bars may be added without anesthesia to enhance stability. Additional pins or significant fracture manipulation would require anesthesia. However, since these are usually open fractures the patient will most likely be returning to the operating room for further debridement.

SOLUTION

We designed a new versatile fixator for long bones that can be implanted easy and in a short time by a relatively simple procedure, can be locked by only 1 clamp screw per element, allows reduction in all directions when it is in place. It is tested for the stability that can withstand bending forces and rotational moments also at a femor site. This unit is consisting of a single bar fixator, 4 (schantz) pins 5mm or 6mm in diameter, and 2 multipin clamps along with insertion instruments. This is to be used at the (Forward Surgical Team) FST level. This system generally conforms with the principles described in the STANAG but is fundamentally different in that it allows fracture realignment independent of pin placement (fig 1 and 2).




Figure 1: Speedfix (Smith&Nephew) 4 screws per fixation element.



Figure 2: "Military Speedfix" Prototype 1 screws per fixation element (Dr.Ing.W.Veith, Heidelberg-Germany).

17 - 2 RTO-MP-HFM-109